



INVESTOR IN PEOPLE

USA

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed  *AmBrewer*

Dated 21 October 2003

THIS PAGE BLANK (USPTO)

OLIFF & BERRIDGE, PLC
P.O. BOX 19928
ALEXANDRIA, VA 22320
(703) 836-6400
APPLICANT: William Edward ROBBINS
APPLICATION NO.: New U.S. Application
FILED: November 25, 2003
FOR: ROTOR BALANCING AND DRIVE SHAFT SIMULATOR
THEREFOR
ATTORNEY DOCKET NO.: 117798

Patents Form 1/77

Patents Act 1977
(Rule 16)

THE PATENT OFFICE

14 JAN 2003

RECEIVED BY FAX

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference PAT/AT/3065

2. Patent application number
(The Patent Office will fill in this part)

0300768.9

14JAN03 E776845-1 D01077
01/7700 0.00-0300768.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ROLLS-ROYCE plc
65 BUCKINGHAM GATE
LONDON
SW1E 6AT
GREAT BRITAIN

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

GREAT BRITAIN

3970002

4. Title of the Invention ROTOR BALANCING AND DRIVE SHAFT SIMULATOR THEREFOR

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MR V J BIRD
INTELLECTUAL PROPERTY DEPT WH 58
ROLLS-ROYCE plc
PO BOX 3
FILTON
BRISTOL
BS34 7QE

Patents ADP number (if you know it)

65789006

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 11

Claim(s) 3

Abstract 0

Drawing(s) 3

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0


Statement of inventorship and right to grant of a patent (Patents Form 7/77) YES

Request for preliminary examination and search (Patents Form 9/77) YES

Request for substantive examination (Patents Form 10/77) NO

Any other documents (please specify) NO

11. I/We request the grant of a patent on the basis of this application.



Signature

Date

V J BIRD

14 JANUARY 2003

12. Name and daytime telephone number of person to contact in the United Kingdom ADAM TINDALL 0117 979 4623
adam.tindall@rolls-royce.com

Warning


After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

Patents Form 7/77

Patents Act 1977
(Rule 15)Statement of Inventorship and of
right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference PAT/AT/3065

2. Patent application number
(if you know it)

0300768.9

3. Full name of the or of each applicant ROLLS-ROYCE plc

4. Title of the invention

ROTOR BALANCING AND DRIVE SHAFT SIMULATOR THEREFOR

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patentBY VIRTUE OF THE INVENTORS' TERMS AND CONDITIONS OF
EMPLOYMENT6. How many, if any, additional Patents Forms
7/77 are attached to this form? NO
(see note (c))

7.

I/We believe that the person(s) named over the page (and on
any extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to.

Signature

Date

V J BIRD

14 JANUARY 2003

8. Name and daytime telephone number of
person to contact in the United KingdomADAM TINDALL 0117 979 4623
adam.tindall@rolls-royce.com

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

☐ Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

WILLIAM EDWARD ROBBINS
73 BATH ROAD
KEYNSHAM
BRISTOL
BS31 1SR

8543225001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents Form 7/77

DUPLICATE

- 1 -

ROTOR BALANCING AND DRIVE SHAFT SIMULATOR THEREFOR

This invention relates to a method of balancing a rotary device for balanced operation when connected to a drive shaft by a flexible coupling, and in particular the invention concerns the use of drive shaft simulators to simulate the effect of the drive shaft on the rotary device during balancing.

Rotary devices such as engines and the auxiliary units that are connected to engines by drive shafts are usually balanced individually with drive shaft simulators to compensate for geometric errors, for example swash and eccentricity, due to misalignment of the rotational axes of the respective rotary devices when connected together by the drive shaft. Balancing of the individual devices provides for interchangeability of the devices so that a modular approach to a manufacture may be employed, that is to say, in theory it should be possible to connect any individually balanced rotary devices by means of a transmission drive shaft without introducing unbalance in the assembled rotary system.

In one method currently employed, drive shaft simulators are rigidly attached to the rotary device to be balanced. This approach introduces errors since the drive shaft being simulated, when assembled with the rotary device, is usually connected to the rotary device via a flexible coupling, with the axis of rotation of the drive shaft being determined by the eccentricity of the drive shaft location features on the rotary devices being connected. This arrangement does not take into account the angular alignment, or swash, of the drive shaft being simulated when connecting the two rotary devices. In this way the drive shaft simulators do not replicate the actual axis of rotation of the installed drive shaft being simulated and hence the simulated unbalance.

In known methods the drive shaft simulators are designed so that the mass, centre of gravity and inertia of the drive shaft simulator is the same as the drive shaft being simulated.

- 2 -

The present inventor has recognised that the use of such drive shaft simulators in the above-mentioned method to simulate drive shafts with flexible coupling can lead to increased vibration in the balanced rotary device since the drive shaft simulators do not replicate the actual axis of rotation of the installed drive shaft being simulated because of the effect of the flexible couplings. In this way the drive shaft simulators incorrectly simulated unbalance. This can lead to increased vibration which may require the rotary device and assembled system to be rebalanced, and in extreme cases can lead to rotor failure due to excessive vibration.

According to an aspect of the invention there is provided a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said method comprising the steps of connecting a drive shaft simulator to the said rotary device and rotating the said device to simulate drive shaft unbalance due to misalignment of the rotary device and the drive shaft being simulated when the drive shaft and rotary device are connected together.

The present inventor has found that it is possible to correctly simulate drive shaft unbalance due to misalignment of the rotary device with respect to the drive shaft being simulated by determining appropriate drive shaft simulator parameters, that is to say the misalignment that occurs in practice due to geometric tolerances and accommodated by the use of flexible couplings. The inventor has shown by rigorous mathematical analysis it is possible to replicate the effects of the drive shaft and flexible coupling in a balancing method where the axis of rotation is the axis of the rotary device. This method therefore overcomes at least in part the problem of rotor and drive shaft balancing using drive shaft simulators which do not correctly replicate the dynamic effects of the drive shaft being simulated as a result of the drive shaft having a slightly different axis of rotation to that of the rotary device when connected together.

The step of stimulating drive shaft unbalance preferably comprises the step of simulating unbalance due to drive shaft eccentricity and/or angular misalignment with respect to the axis of the rotary device.

- 3 -

Preferably, the mass of the drive shaft simulator is substantially half the mass of the drive shaft to be simulated. By having the mass of the drive shaft simulator substantially equal to half the mass of the drive shaft being simulated, the drive shaft unbalance due to the effects of drive shaft eccentricity can be correctly simulated in the balancing method according to embodiments of the invention. This is a significant development in the art of balancing rotary devices since hitherto established practice has involved the use of full mass drive shaft simulators, that is drive shaft simulators having a mass substantially equal to that of the drive shaft being simulated. The present inventor has found by fundamental mathematical analysis that the effects of eccentricity can be correctly simulated by using half mass drive shaft simulators in the balancing method disclosed herein.

Preferably, the said drive shaft simulator has a polar moment of inertia substantially equal to its diametral moment of inertia and is positioned with respect to the rotary device such that its centre of gravity is substantially coincident with the plane of flexibility of the flexible coupling, which in use, connects the rotary device to the drive shaft being simulated, whereby to simulate the effect of angular misalignment of the drive shaft being simulated with respect to the axis of the rotary device. The present inventor has demonstrated that by connecting the drive shaft simulator to the rotary device being balanced such that the centre of gravity of the drive shaft simulator is coincident with the interface plane or plane of flexibility between the rotor and drive shaft being simulated, and designing the simulated drive shaft such that its polar moment of inertia and diametral moment of inertia are equal, the drive shaft unbalance due to swash at the interface of the rotary device and drive shaft arising from angular misalignment can be correctly simulated.

In preferred embodiments, the method further comprises the step of determining the balancing correction to be applied to the rotary device for balanced operation of the rotary device when connected to a drive shaft of the type being simulated by a flexible coupling. This provides for balanced operation in use and readily permits interchangeability of rotary device and drive shaft components for maintenance

- 4 -

purposes and the like when connected together in a power transmission system.

Preferably the rotary device comprises an engine or a device driven by an engine via a transmission including for example a drive shaft of the type being simulated. The term "rotary device" used herein, therefore, contemplates embodiments where the rotary device is an engine, having a power output shaft for instance, or an auxiliary device that is driven by power from the engine and having its own rotary components.

In one embodiment the rotary device comprises a gas turbine engine or module thereof, or an auxiliary device to be driven by the engine or engine module via a drive shaft of the type being simulated. The invention therefore contemplates embodiments where the auxiliary rotary device comprises an oil pump, a fuel pump, an alternator or a lift fan, for example, where the engine is an aero gas turbine engine. In industrial gas turbine engine applications power take-off shafts are commonly used for driving alternators either directly or indirectly via a gearbox, and in marine gas turbine engine applications power take-off shafts are used for driving propeller shafts, directly or indirectly via a gearbox or for driving alternators. The method of the present invention is applicable to other fields of technology and may be employed to correctly simulate drive shaft behaviour in balancing methods where it is necessary to balance individual rotary devices that are to be connected to a respective end of a drive shaft by means of a flexible coupling, and therefore the invention finds particular application wherever correct balancing of rotary devices in modular component systems is important.

According to another aspect of the invention there is provided a method of balancing a rotary device for balanced rotational operation in a rotary device and drive shaft assembly in which a drive shaft is connected to a rotary device by a flexible coupling; the said method comprising the steps of connecting a drive shaft simulator to the said rotary device; the drive shaft simulator having substantially half the mass of the drive shaft to be simulated and a polar moment of inertia substantially equal to its diametral moment of inertia, the drive shaft simulator being positioned with respect to the rotary device such that its centre of gravity is substantially coincident with the plane of flexibility of a flexible coupling, which in use, connects the rotary device to the drive

- 5 -

shaft being simulated, whereby to determine a balancing correction to be applied to the said rotary device for balanced operation when connected to a drive shaft of the type being simulated by a flexible coupling.

According to a further aspect of the invention there is provided a drive shaft simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said drive shaft simulator having substantially half the mass of the drive shaft to be simulated.

According to another aspect of the invention there is provided a drive shaft balancing simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the drive shaft simulator having a polar moment of inertia substantially equal to its diametral moment of inertia.

According to another aspect of the invention there is provided a drive shaft balancing simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said drive shaft simulator having substantially half the mass of the drive shaft to be simulated and a polar moment of inertia substantially equal to its diametral moment of inertia.

An embodiment of the invention will now be more particularly described, by way of example only with reference to the accompanying drawings in which:

Figure 1 is a schematic representation of an engine and auxiliary unit connected together by means of a drive shaft and flexible couplings;

Figure 2 is a schematic representation of the engine and auxiliary unit of Figure 1 configured for balancing with appropriate drive shaft simulators;

Figure 3 is a schematic representation of the components shown in Figure 1 showing various rotary device and drive shaft parameters for determining simulated

- 6 -

unbalance due to eccentricity of drive shaft location features on the engine and auxiliary unit;

Figure 4 is a schematic representation similar to that of Figure 3 showing various parameters for determining simulated unbalance due to swash (angular misalignment) of drive shaft location features on the engine and auxiliary units.

Referring to Figure 1, which shows a transmission system 10 connecting a first rotary device 12, for example an engine which may be a gas turbine engine, to an auxiliary rotary device 14. In the arrangement the engine has an axis of rotation 16 which defines the axis of rotation of an engine output shaft 18. The auxiliary rotary device 14 also has an axis of rotation 20 which defines the axis of rotation of an input shaft 22. The auxiliary device 14 may be an oil pump, fuel pump, alternator or any other device that is capable of being driven by the engine 12. The engine and auxiliary devices are connected together by means of a drive shaft 24 and respective flexible couplings 26 and 28 which connect to the engine and auxiliary device respectively. In the drawing of Figure 1 the engine axis 16 and auxiliary axis 20 are slightly misaligned due to build tolerances and the like and hence the drive shaft 24 has an axis 30 which is inclined with respect to both the axis 16 and 20. The angular misalignment of the drive shaft axis 13 with respect to the engine and auxiliary axes is accommodated by the flexible couplings 26 and 28 at the ends of the drive shaft.

The arrangement of Figure 1 is typical of any transmission system where a drive shaft is used to connect an engine or other rotary prime mover type device to a driven device such as the auxiliary unit 14 in the drawings of Figure 1. This arrangement is commonly found in gas turbine engine arrangements where engine auxiliary devices such as oil pumps, fuel pumps, etc, are connected to the engine by means of a radial drive shaft.

Referring now to Figure 2, in a method of balancing the rotary devices 12 and 14 so that they are individually balanced for interchangeability purposes, the engine drive shaft interface 18 is connected to a first drive shaft simulator 32 which simulates the

- 7 -

effect of the drive shaft 24 on the engine during balancing, and similarly a drive shaft simulator 34 is connected to the input drive shaft interface 22 of the auxiliary unit 14. The drive shaft simulators 32 and 34 have a mass equal to half that of the drive shaft 24 such that the combined mass of the drive shaft simulators 32 and 34 is equal to the mass of the drive shaft 24. For both drive shaft simulators 32 and 34 the polar moment of inertia is equal to the diametral moment of inertia of that simulator. The drive shaft simulator 32 is connected to the engine interface shaft 18 in such a way that its centre of gravity 36 is positioned coincident with the plane of flexibility of the flexible coupling 26 at one end of the drive shaft, as defined by the plane perpendicular to the engine axis 16 at the point of intersection 38 with the drive shaft axis 30 at the drive shaft interface of coupling 26. Positioning the centre of gravity of the drive shaft simulator 32 so that it is coincident with the plane of flexibility of the drive shaft coupling 26 enables the effect of the drive shaft 24 to be correctly simulated when the engine and drive shaft simulator 32 are rotated about the engine axis 16. This occurs despite the fact that the drive shaft being simulated is angled with respect to the axis 16 in the arrangement of Figure 1. This will be more clearly appreciated from the mathematical analysis of the system that is to follow. It is to be understood that the drive shaft simulator 34 is connected to the auxiliary rotary unit 14 in the same way to that of simulator 32, in the sense that its centre of gravity is positioned coincident with the plane of flexibility defined by the plane perpendicular to the auxiliary axis 20 positioned at the point of intersection 39 between the drive shaft axis 30 and auxiliary axis 20.

In the balancing method of the invention the engine 12 and simulator drive shaft 32 are rotated about the engine axis 16 in order to simulate the effects of the drive shaft 24. This enables a balancing correction to be determined and applied to the rotating components of the engine 16 for the purpose of interchangeability, and similarly for the auxiliary unit 14.

There now follows a description of the mathematical analysis which demonstrates the theory which underlies aspects of the present invention. First, reference is made to correctly simulating the effects of drive shaft eccentricity, and second the effects of simulating drive shaft unbalance due to the effects of swash. In the context of the

- 8 -

present description the term "swash" refers to the angular misalignment of the drive shaft 24 being simulated with respect to the axis of rotation of the rotary device to be balanced, that is to say engine axis 16 or auxiliary axis 20.

Eccentricity

Referring now to Figure 3, interchangeability is achieved by making eccentric unbalance simulated by both engine and auxiliary unit drive shaft locations equal to that of the installed drive shaft. This can be represented by the following vector equations;

$$UE_{eau} = UE_e + UE_{au}$$

Where:

UE_{eau} = Drive Shaft Unbalance due to eccentricity of location features on the engine and auxiliary unit.

UE_e = Simulated drive shaft unbalance due to eccentricity of location features on the engine.

UE_{ae} = Simulated drive shaft unbalance due to eccentricity of location features on the auxiliary unit.

Assuming ridged rotor theory applies.

With reference to Figure 3:

$$UE_{eau} = M_{ds} \times E_{ds}$$

$$UE_e = M_s \times E_e$$

$$UE_{au} = M_s \times E_{au}$$

Where the following definitions are vector quantities:

M_{ds} = Mass of the drive shaft

E_{ds} = Eccentricity of installed drive shaft CofG

M_s = Mass of the drive shaft simulator/s

E_e = Eccentricity of drive shaft simulator due to engine location feature

E_{au} = Eccentricity of drive shaft simulator due to auxiliary unit location feature

$$E_{ds} = \{[E_e + E_{au}] / 2\} - E_{au}$$

$$E_{ds} = E_e/2 + E_{au}/2 - E_{au}$$

$$E_{ds} = E_e/2 - E_{au}/2$$

- 9 -

$$2E_{ds} = E_e - E_{au}$$

Therefore

$$U_{E_{au}} = U_{E_e} + U_{E_{au}}$$

$$M_{ds} \times E_{ds} = M_s \times E_e + M_s \times E_{au}$$

$$M_{ds} \times E_{ds} = M_s \times E_e - M_s \times E_{au}$$

$$M_{ds} \times E_{ds} = M_s [E_e - E_{au}]$$

Substitute $E_e - E_{au} = 2E_{ds}$

$$M_{ds} \times E_{ds} = 2E_{ds}M_s$$

$$M_s = M_{ds}/2$$

In summary, the mass of the drive shaft simulators 32, 34 must each equal half the mass of the drive shaft to accurately simulate drive shaft unbalance due to eccentricity of engine and auxiliary unit drive shaft location features.

Swash

Referring to Figure 4, interchangeability is achieved by making swash unbalance simulated by both engine and auxiliary unit drive shaft locations equal to that of the installed drive shaft. This can be represented by the following vector equations:

$$U_{Seau} = U_{Se} + U_{Sau}$$

where

U_{Seau} = Drive Shaft Unbalance due to swash of location features on the engine and auxiliary unit.

U_{Se} = Simulated drive shaft unbalance due to swash of location features on the engine.

U_{Sau} = Simulated drive shaft unbalance due to swash of location features on the auxiliary unit.

Assuming ridged rotor theory applies.

With reference to Figure 4

$$U_{Seau} = [M \times SE_{ds}] + \{\delta[l_{pds} - l_{dds}]\}$$

- 10 -

$$USe = [Ms \times SEe] + \{\alpha[lp - Id]\}$$

$$USau = [Ms \times SEau] + \{\beta[lp - Id]\}$$

Where the following definitions are vector quantities:

M = Mass of drive shaft

SEds = Eccentricity of installed drive shaft due to swash of engine and auxiliary unit Interfaces

δ = Swash angle of installed drive shaft 'axis of rotation' relative to that of the shaft, auxiliary unit and

engine, combined, in radians

lpds = Polar moment of inertia of drive shaft

ldds = Diametral moment of inertia of drive shaft

Ms = Mass of drive shaft simulator

SEe = Eccentricity of simulated drive shaft due to swash of engine Interface

α = Swash angle of simulated drive shaft 'axis of rotation' relative to that of the engine, in radians

lp = Polar moment of inertia of simulated drive shaft

ld = Diametral moment of inertia of simulated drive shaft

SEau = Eccentricity of simulated drive shaft due to swash of auxiliary unit Interface

β = Swash angle of simulated drive shaft 'axis of rotation' relative to that of the auxiliary unit, in radians.

For the installed drive shaft δ equals zero due to the effect of the flexible couplings.

With δ equal to zero SEds also equals zero.

$$USeau = [M \times SEds] + \{\delta[lpds - ldds]\}$$

$$USeau = [M \times 0] + \{0[lpds - ldds]\}$$

$$USeau = 0$$

From $USeau = USe + USau$, USe and USau must equal zero.

$$USe = [Ms \times SEe] + \{\alpha[lp - Id]\} = 0 \text{ and}$$

$$USau = [Ms \times SEau] + \{\beta[lp - Id]\} = 0$$

By making the simulated drive shaft CofG coincide with the plane of flexibility between

- 11 -

engine/auxiliary unit and the simulated drive shaft, both SE_e and SE_{au} will equal zero and hence eccentricity due to swash will be equal to zero. The plane of flexibility is defined by the plane perpendicular to the engine/auxiliary unit 16,20 at the point of intersection 38,39 between the drive shaft axis 30 and engine/auxiliary unit 16,20.

By making the drive shaft simulator inertia's, I_p and I_d , equal to each other, couple unbalance due to swash will equal zero.

In summary, the CofG of the drive shaft simulator must coincide with the plane of flexibility between engine/auxiliary unit and the simulated drive shaft, and the simulated drive shaft inertia's, polar and diametral, must be equal to each other to simulate drive shaft unbalance due to swash of engine.

Although aspects of the invention have been described with reference to the embodiments shown in the accompanying drawing, it is to be understood that the invention is not limited to this precise embodiment and that various changes and modifications may be effected without further inventive skill and effort.

- 12 -

CLAIMS

- 1 A method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said method comprising the steps of connecting a drive shaft simulator to the said rotary device and rotating the said device to simulate drive shaft unbalance due to misalignment of the rotary device and the drive shaft being simulated when the drive shaft and rotary device are connected together.
- 2 A method as claimed in Claim 1 wherein the step of simulating drive shaft unbalance comprises simulating unbalance due to drive shaft eccentricity and/or angular misalignment with respect to the axis of the said rotary device.
- 3 A method as claimed in Claim 1 or Claim 2 wherein the mass of the said drive shaft simulator is substantially half the mass of the drive shaft to be simulated, whereby to simulate the effect of drive shaft eccentricity.
- 4 A method as claimed in Claims 1 to 3 wherein the said drive shaft simulator has a polar moment of inertia substantially equal to its diametral moment of inertia and is positioned with respect to the rotary device such that its centre of gravity is substantially coincident with the plane of flexibility of the flexible coupling, which in use, connects the rotary device to the drive shaft being simulated, whereby to simulate the effect of angular misalignment of the drive shaft being simulated with respect to the rotary device.
- 5 A method as claimed in any preceding claim further comprising the step of determining a balancing correction to be applied to the said rotary device for balanced operation of the said rotary device when connected to a drive shaft of the type being simulated by a flexible coupling.
- 6 A method as claimed in any preceding claim wherein the said rotary device

- 13 -

comprises an engine or a device to be driven by the said engine and a drive shaft of the type being simulated.



- 7 A method as claimed in any preceding claim wherein the said rotary device comprises a gas turbine engine or engine module thereof, or an auxiliary device to be driven by the said engine and a drive shaft of the type being simulated.
- 8 A drive shaft simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said drive shaft simulator having substantially half the mass of the drive shaft to be simulated.
- 9 A drive shaft balancing simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the drive shaft simulator having a polar moment of inertia substantially equal to its diametral moment of inertia.
- 10 A drive shaft balancing simulator for use in a method of balancing a rotary device for balanced rotational operation when connected to a drive shaft by a flexible coupling; the said drive shaft simulator having substantially half the mass of the drive shaft to be simulated and a polar moment of inertia substantially equal to its diametral moment of inertia.
- 11 A method of balancing a rotary device for balanced rotational operation in a rotary device and drive shaft assembly in which a drive shaft is connected to a rotary device by a flexible coupling; the said method comprising the steps of connecting a drive shaft simulator to the said rotary device; the drive shaft simulator having substantially half the mass of the drive shaft to be simulated and a polar moment of inertia substantially equal to its diametral moment of inertia, the drive shaft simulator being positioned with respect to the rotary device such that its centre of gravity is substantially coincident with the plane of flexibility of a flexible coupling, which in use, connects the rotary device to the

- 14 -

drive shaft being simulated, whereby to determine a balancing correction to be applied to the said rotary device for balanced operation when connected to a drive shaft of the type being simulated by a flexible coupling.

- 12 A method substantially as hereinbefore described and/or with reference to the accompanying drawings.
- 13 A drive shaft balancing simulator substantially as hereinbefore described and/or with reference to the accompanying drawings.

1/3

Figure 2FIGURE 1

THIS PAGE BLANK (USPTO)

Illustration of Simulated Unbalance due to Eccentricity of Drive Shaft
Location Features on the Engine/Auxiliary Unit




Fig 3

THIS PAGE BLANK (USPTO)

3/3

Illustration of Simulated Unbalance due to Swash of Drive Shaft
Location Features on the Engine/Auxiliary Unit




FIG 4

THIS PAGE BLANK (USPTO)